



ME13-DY01-1000



## Features

### Folding handle

Folding push handle can be folded down so mower can be stored in less space.

### Easy starting

High-Quality motor and well designed switch make the lawnmower safe and reliable.

### Easy controlling

Light weight design makes mower easy to push and maneuver in the lawn.

### Easy assembly

Easy to assemble. No tools required.

## Technical Specification

Drive type	Hand Push
Engine type	AC Motor
Rated Voltage	230 V
Rated Power	1000W
Rated Speed	2900rpm
Cutting Height	23-56mm 4grades
Height Adjustment	4 wheel independent adjustment
Cutting Path	320mm (13")
Wheel Diameter	Front wheel 128mm(5") Rear wheel 156mm(6")
Wheel Width	Front wheel 36mm Rear wheel 50mm
Catcher Volume	27L
Deck Material	Plastic
Noise Level	94 db
Max. Permissible Slope	15deg
Product measurement	1065x420x1000mm
Carton Measurement	615x388x3350mm
Approvals	CE GS EMC
N.W/G.W	10.1.5kg/12.5kg



The wheels are easy to disassemble. height adjustment is convenient.



Blade is made of hi-quality manganese steel, sharpness and tough hardness

DY164PMBS



## Features

### Folding handle

Folding push handle can be folded down so mower can be stored in less space.

### Hi-quality engine

High-quality engine, 4-stroke, forced air cooling, auto-reducing pressure and digit ignition system.

### Easy controlling

Light weight design makes mower easy to push and maneuver in the lawn.

### Deck and Blade

High quality plastic deck make the mower light. Manganese steel blade is sharp and hard to give better cutting efficiency.

## Technical Specification

Drive type	Hand Push
Engine	4-Stroke, Forced air Cooling single cylinder, OHV
Max. Torque	7.0 N.M/2800rpm
Max. Power	2600W(4ps)3600rpm
Rated Power	2050(3ps)
Rated Speed	2750rpm
Displacement	118cc
Starting	Recoil
Tank Volume	1.5L
Cutting Height	30-63mm 3grades 25-75mm 5 grades
Height Adjustment	4 wheel independent adjustment 4 lever independent adjustment
Cutting Path	406mm
Wheel Diameter	152mm(6")
Wheel Width	42mm
Catcher Volume	50L
Deck Material	Plastic
Max. Permissible Slope	15deg
Product measurement	1320x440x1000mm
Carton Measurement	760x468x435
Approvals	CE GS EMC
N.W./G.W	23.5kg/26kg



It is convenient to start the engine without stop



Blade is made of hi-quality manganese steel, sharpness and tough hardness

DY 184SMBS



## Features

### Folding handle

Folding push handle can be folded down so mower can be stored in less space.

### Hi-quality engine

High-quality engine, 4-stroke, forced air cooling, auto-reducing pressure and digit ignition system.

### Easy controlling

Light weight design makes mower easy to push and maneuver in the lawn.

### Deck and Blade

High quality plastic deck make the mower light. Manganese steel blade is sharp and hard to give better cutting efficiency.

Drive type	Self-propelled
Engine	4-Stroke, Forced air cooling single cylinder, OHV
Max. Torque	7.0 N.M/2800rpm
Max. Power	2600W(4ps)3600rpm
Rated Power	2050(3ps)
Rated Speed	2750rpm
Displacement	118cc
Starting	Recoil
Tank Volume	1.5L
Cutting Height	25-75mm 5grades
Height Adjustment	One Lever Adjustment
Cutting Path	459mm
Wheel Diameter	Front wheel 152mm(6") Rear wheel 206mm(8")
Wheel Width	Front Wheel 42mm Rear Wheel 50mm
Walking Speed	4Km/h
Catcher Volume	55L
Deck Material	Steel
Max. Permissible Slope	15deg
Product measurement	1500x520x1030mm
Carton Measurement	820x540x465
Approvals	CE GS EMC
N.W/G.W	37kg/40kg



It is convenient to start the engine without stop



Blade is made of hi-quality manganese steel, sharpness and tough Hardness



## Brush Cutter

**Model : N1B-MDL01-M09**  
Voltage: 230V-50Hz  
No load speed: 12000rpm  
Cutting diameter: 230mm  
Single nylon line bump or manual feed system: 1.4mmX5.5m  
Light weight design, detached to 2 sections  
Easy change from cutting trimming to edge trimming  
GS/EMC/CE/ETL approved

## Grass Trimmer

**Model : MG3001**  
Voltage: 230V-50Hz  
No load speed: 10000rpm  
Cutting diameter: 300mm  
Telescopic metal shaft  
Swivel head with guide wheels for easy edge trimming  
Soft grip handle for extra comfort  
Twin nylon line bump feed system: 1.4mmx8mm  
Adjustable secondary handle  
GS/EMC/CE/ETL approved

## Grass Trimmer

**Model :N1B-MDL02-14+W**  
Voltage: 230V-50HZ, no load speed: 9000rpm  
Cutting diameter: 350mm  
Grass trimmer performs like a lawn mower with 2 additional wheels. Detachable and adjustable wheels with 3 different cutting height  
Telescopic metal shaft Swivel and titled head with guide wheels for easy edge trimming  
Soft grip handle for extra comfort  
Twin nylon line bump feed system  
Adjustable secondary handle  
GS/EMC/CE approved

## Vacuum Blower

Voltage: 230V-50HZ  
No load speed: 13000rpm  
Max air speed: 270km/h  
Min air speed: 180km/h  
Max air volume: 14cbm/h  
Combining blowing, vacuum, shredding function together  
2 speed, shoulder strap supported  
35L collect bag  
GS/EMC/CE approved

# WHEEL BARROW CANVAS TROLLEY



## Features

Light weight, with great strength.  
Used in many applications as per your requirements.

## Specifications :

Model	Capacity	Wheel Castors	Height		Width		Length		Vol.
			(H)	(H)	(W)	(L)	(l)		
	kg	mm	mm	mm	mm	mm	mm	Ltrs	
WB7401	110	350	510	298	636	1455	898	78	
TC 1131	25	250	865	480	625	1080	785		

## LOKPAL INDUSTRIES

A-6, Sector-3, Noida-201301, U.P., India | Tel.: +91-120-3065372 / 75

Website: [www.lokpal.com](http://www.lokpal.com) | E-mail: [info@lokpal.com](mailto:info@lokpal.com)